

**BSOZAA40Z**


**AVALANCHE VOLTAGE**    **24 to 32 Volts**  
**CURRENT**                **40 Amperes**

**Technical Specification:**
**Features:**

- High power capability
- Economical
- Avalanche Voltage: 24V to 32V

**MECHANICAL DATA**

- Copper slug
- Polarity: colour dots denotes cathode end
- Technology vacuum soldered
- Mounting position: Any
- Weight: 0.0219 ounce, 0.62 Grams


**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

Electrical Characteristics @ 25°C	SYMBOLS	MIN	NOMINAL	MAX	UNITS
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>		20		
Working Peak Reverse Voltage	V <sub>RRM</sub>		20		Volts
DC Blocking Voltage	V <sub>DC</sub>		20		
Average Rectified Forward Current (Tc=125°C)	I <sub>o</sub>		40		Amps
Repetitive Peak Reverse Surge Current Tc=10msec Duty Cycle<1%	I <sub>RSM</sub>		40		Amps
Breakdown Voltage (Vbr@ir=100mA, Tc=25°C) Ir=90Amps, Tc=150°C, PW=80usec	V <sub>b1</sub> V <sub>b2</sub>	24	25-27	32 40	Volts Volts
Forward Voltage Drop @If=100Amps<300usec	V <sub>F</sub>		1.0	1.05	Volts
Peak Forward Surge Current	I <sub>FSM</sub>		500		Amps
Reverse Leakage (V <sub>R</sub> =17Vdc) T <sub>A</sub> =25°C	I <sub>R</sub>		1.0	2.0	uAmps
Operating and Storage Junction Temperature Range	T <sub>J</sub> , T <sub>STG</sub>		-65 to +175		°C

**Notes:** 1. Enough heatsink must be considered in application.

